


Top-Open

颜色:

本色

兰色

灰色



Bottom-Open

颜色:

本色

兰色

灰色

MAX TRON



OPERATING SPECIFICATIONS

MAX .PRESSURE 150 PSI (10.5 BAR)

MAX .TEMPERATURE 49°C (120° F)

MIN. TEMPERATURE 1C (34F)

MAX . VACUUM 127mm Hg(5" Hg)

No.	Size		Diameter		Height Without Base		Height With Base		Top Open	Bottom Open	Capacity		Operating Pressure		Filtration Velocity m³/h
	(In)	(mm)	(In)	(mm)	(In)	(mm)	(In)	(mm)			Gallons	Liters	MPa	BAR	
1	07×13	Φ170×330	7.0	181	12.6	320	13.0	330	2.5"Threaded	/	1.8	7.0	1.0	10.0	0.2~0.3
2	07×24	Φ170×610	7.0	181	24.0	610	25.4	640	2.5"Threaded	/	3.8	15.0	1.0	10.0	0.2~0.3
3	07×35	Φ170×890	7.0	181	35.0	890	36.4	920	2.5"Threaded	/	5.2	19.7	1.0	10.0	0.2~0.4
4	08×17	Φ200×430	8.0	206	17.0	430	18.1	465	2.5"Threaded	/	3.1	11.7	1.0	10.0	0.2~0.5
5	08×20	Φ200×470	8.0	206	19.0	470	19.5	495	2.5"Threaded	/	3.5	13.4	1.0	10.0	0.1~0.3
6	08×35	Φ200×890	8.0	206	35.0	890	36.2	920	2.5"Threaded	/	6.6	25.0	1.0	10.0	0.1~0.3
7	08×44	Φ200×1115	8.0	206	43.9	1115	44.9	1140	2.5"Threaded	/	8.7	32.9	1.0	10.0	0.2~0.5
8	09×35	Φ220×890	9.0	232	35.0	890	35.8	910	2.5"Threaded	/	8.3	31.4	1.0	10.0	0.2~0.5
9	09×40	Φ220×1005	9.0	232	40.0	1005	40.4	1025	2.5"Threaded	/	9.5	36.0	1.0	10.0	0.2~0.5
10	09×48	Φ220×1215	9.0	232	48.0	1215	48.4	1230	2.5"Threaded	/	12.7	48.0	1.0	10.0	0.3~0.6
11	10×17	Φ240×430	10.0	257	17.0	430	18.1	460	2.5"Threaded	/	4.8	18.2	1.0	10.0	0.2~0.4
12	10×35	Φ240×890	10.0	257	35.0	890	36.0	915	2.5"Threaded	/	10.2	38.6	1.0	10.0	0.5~1.0
13	10×44	Φ240×1115	10.0	257	43.9	1115	45.1	1145	2.5"Threaded	/	13.1	49.6	1.0	10.0	0.5~1.4
14	10×54	Φ240×1375	10.0	257	54.1	1375	55.3	1405	2.5"Threaded	/	16.4	62.0	1.0	10.0	0.6~1.5
15	12x48	Φ300×1215	12.0	308	48.0	1215	49.4	1225	2.5"Threaded	/	20.6	78.0	1.0	10.0	1.6~2.0
16	12×52	Φ300×1320	12.0	308	52.0	1320	53.3	1355	2.5"Threaded	/	22.2	84.0	1.0	10.0	1.6~2.2
17	12×65	Φ300×1620	12.0	308	52.0	1620	65.9	1675	2.5"Threaded	/	22.6	112.0	1.0	10.0	1.8~2.4
18	13×54	Φ330×1370	13.0	334	54.0	1370	55.3	1405	2.5"Threaded	/	27.5	104.0	1.0	10.0	2.0~2.5
19	14×65	Φ350×1620	14.0	360	63.8	1620	65.6	1665	2.5"Threaded	/	40.6	154.0	1.0	10.0	2.5~3.0
20	14×65	Φ350×1620	14.0	360	63.8	1620	65.6	1665	4" Threaded	/	40.6	154.0	1.0	10.0	2.5~3.0
21	16×65	Φ400×1620	16.0	410	63.8	1620	64.6	1640	2.5"Threaded	/	49.0	185.0	1.0	10.0	3.2~4.5
22	16×65	Φ400×1620	16.0	410	63.8	1620	64.6	1640	4" Threaded	/	49.0	185.0	1.0	10.0	3.2~4.5
23	16×65	Φ400×1620	16.0	410	63.8	1620	72.3	1840	4" Threaded	4" Threaded	49.0	185.0	1.0	10.0	3.2~4.5
24	18×65	Φ450×1620	18.0	460	63.8	1620	72.2	1835	4" Threaded	/	66.7	251.8	1.0	10.0	3.5~4.8

25	18×65	Φ450×1620	18.0	460	63.8	1620	72.2	1835	4" Threaded	4" Threaded	66.7	251.8	1.0	10.0	3.5~4.8
26	21×62	Φ530×1600	21.7	550	63.0	1600	72.5	1842	4" Threaded	/	88	333	1.0	10.0	4.1~5.6
27	21×62	Φ530×1600	21.7	550	63.0	1600	72.5	1842	4" Threaded	4" Threaded	88	333	1.0	10.0	4.1~5.6
28	24×72	Φ600×1800	24.4	620	70.9	1800	80.4	2042	4" Threaded	4" Threaded	126.8	480	1.0	10.0	6.2~8.2
29	30×72	Φ750×1800	30.5	775	70.9	1800	80.5	2045	4" Threaded	4" Threaded	195.5	740	1.0	10.0	7.2~12.2
30	36×72	Φ900×1800	36.4	925	70.9	1800	84.4	2145	4" Threaded	4" Threaded	283.0	1071	1.0	10.0	13.2~16.2
31	40×72	Φ1000×1800	40.4	1025	70.9	1800	83.5	2120	6"FLG	6"FLG	338.7	1282	1.0	10.0	16.2~22.2
32	42×72	Φ1050×1800	41.4	1050	77.0	1955	89.4	2270	6"FLG	6"FLG	393	1490	1.0	10.0	18-24
33	48×72	Φ1200×1800	48.2	1225	70.9	1800	81.1	2060	6"FLG	6"FLG	477.7	1808	1.0	10.0	22~27
34	48×96	Φ1200×2400	48.2	1225	94.5	2400	104.7	2660	6"FLG	6"FLG	657.1	2487	1.0	10.0	30~40
35	56×96	Φ1400×2400	56.3	1430	94.5	2400	109.4	2780	6"FLG	6"FLG	844.1	3195	0.8	8	35~45
36	60×96	Φ1500×2400	60.2	1530	94.5	2400	109.4	2780	6"FLG	6"FLG	958.0	3626	0.8	8	40~55
37	65×110	Φ1600×2800	64.6	1640	110.2	2800	126.0	3200	6"FLG	6"FLG	1290.1	4883	0.8	8	60~70
38	72×110	Φ1800×2800	72.4	1840	110.2	2800	128.3	3260	6"FLG	6"FLG	958.0	6364	0.8	8	70~80
39	80×126	Φ2000×3200	80.3	2040	126.0	3200	145.7	3700	6"FLG	6"FLG	2404.0	9099	0.8	8	80~90
40	89×126	Φ2200×3200	88.6	2250	126.0	3200	145.7	3700	6"FLG	6"FLG	2846.2	10773	0.8	8	90~100
41	96×126	Φ2400×3400	96.5	2450	133.9	3400	157.5	4000	15"Manway	15"Manway	3228	12218	0.8	8	100~110
42	108×126	Φ2750×3200	110.2	2800	126.0	3200	162.0	4114	15"Manway	15"Manway	4095	15500	0.8	8	110~120
43	120×126	Φ3000×3500	120.5	3060	137.8	3500	171.5	4355	15"Manway	15"Manway	5043.3	19089	0.8	8	120~140

HANDLING INSTRUCTIONS :

VESSEL APPROVED FOR WATER FILTRATION USE ONLY. ALL OTHER APPLICATIONS MUST BE APPROVED BY MANUFACTURER. DO NOT USE FOR PNEUMATIC OR HYDROPNEUMATIC APPLICATIONS. VESSEL MUST NOT BE EXPOSED TO TEMPERATURE BELOW -29C (-20F)

* COMPLY ALL REQUIREMENTS OF P.E.D. 97/23/EC DIRECTIVE

** SUITABLE FOR DRINKING WATER

The Design, Production and Service of this Water Treatment Vessel is in conformity with GB/T19001 - 2000 (idt ISO9001:2000) standard.

